

SMALL SIZE BIG TECHNOLOGY C3320 / C3330

Canon imageRUNNER ADVANCE



Compact and powerful with features and functionality completely new to the Canon range.

The C3320 and C3330 A3 Colour devices are the most compact in the A3 imageRUNNER ADVANCE lineup, with the same advanced workflow and finishing options you come to expect with a Canon product. These clever, versatile devices are suitable for a broad range of customers, from SMBs to large enterprises.

Performance

Superior V2 Colour, superb print quality and new ECO Stapling and Staple On Demand capabilities. When consumables need replacing, video tutorials guide users with Video Support on User Interface (UI).



Integration

Seamlessly integrate with key software solutions from the Canon portfolio and link to other imageRUNNER ADVANCE devices on the same network.



Sustainability

C3320 and C3330 incorporate recycled material and bioplastics, Energy Star qualified, front runner TEC rating. Lower your energy consumption with 1W sleep mode.



Cost Control

Monitor, track and analyse printer activities directly from a desktop computer or the cloud and apply policies to restrict usage if needed.



Security

Multi-layered security solutions safeguard information and support compliance. HDD Data Erase protects user data and the Trusted Platform Module (TPM) function protects sensitive data such as passwords.



At a glance

- A3 multi-function device with a small footprint and greater uptime
- Copy and print in B/W and V2 Colour at 30ppm
- Staple, booklet, ECO Staple and Staple On Demand finishing capabilities



- 7" (17.8cm) full-colour WVAG LCD display touch screen
- Document Scan Lock function prevents unauthorised copy
- Full MEAP capabilities to increase workflows and increase productivity
- Improved visibility and Reminder LED to reduce forgotten originals

Canon

*achieve more.
beyond technology.*

imageRUNNER ADVANCE C3320 / C3330



Basic Specifications

Operation Panel	7" Colour WVGA LCD display
Memory	Standard 2GB Hard Disk Drive 250GB
Network Interface Connection	Ethernet 10Base-T/100Base-TX/1000Base-T
Other Interface (Standard)	USB 2.0 (Host) x 3, USB 2.0 (Device) x 1
Copy/Print Speed	C3330: Up to 30ppm C3320: Up to 20ppm
First-Copy-Out Time	C3330/C3320: 8.2sec Colour / 5.9sec B&W
Paper Sources	Standard: 1,200 sheets Optional: Additional 2 x 550 sheet cassettes (Cassette Feeding Unit) Maximum: 2,300 sheets
Output Paper Capacity	250 sheets (80gsm)
Finishing Capabilities	Standard: Group, Collate Optional Staple Finisher: Group, Collate, Staple
Warm-up Time	From Power On: 34 seconds or less From Sleep Mode: 10 seconds or less Quick Startup Mode: 10 seconds or less
Power Requirements	220-240V, 50/60Hz, 4.0A
Power Consumption	Maximum: 1.5kw Sleep Mode: 1W or less ¹ Energy Star Qualified: Yes
Dimensions (W x D x H)	Main Unit: 565mm x 693mm x 878mm
Installation Space (W x D)	Main Unit: 1,957mm x 1,717mm Main Unit with External Finisher: 2,607mm x 1,717mm
Weight	Approx. 63.2kg (without toner)
Toner (Estimated Yield at 5% Coverage)	Colour: 19,000 Black: 36,000
Cassette/s	Thin paper, Plain paper, Recycled paper, Colour paper

Print Specifications (Standard)

Printing Resolution	1200 x 1200dpi
PDL Support	Standard: UFR II Optional: PS & PCL
Acceptable Paper Type	Heavy paper, Pre-punched paper, Envelopes ² , Pre-punched paper, Transparency, Labels, Envelopes (No.10 (COM10), Monarch, ISO-C5, DL), Tracing Paper, Bond
Acceptable Paper Sizes	Cassette 1: A4, B5, A5R, LTR, STMTR, EXEC, Custom size (139.7 x 182 mm to 297 x 215.9 mm), and Envelopes (ISO-C5) Cassette 2, 3 and 4: A3, B4, A4, A4R, B5, B5R, A5R, 12" x 18", 11" x 17", LGL, LTR, LTRR, STMTR, EXEC, FOLIO, A-LTR, A-LTRR, ILGL, AFLS, FLS, Custom size (139.7 x 182 mm to 304.8 x 457.2 mm), and Envelopes (Monarch, COM10 No.10, DL) Manual Feed: A3, B4, A4, A4R, B5, B5R, A5, A5R, 12" x 18", 11" x 17", LGL, LTR, LTRR, STMTR, EXEC, FOLIO, A-LTR, A-LTRR, ILGL, AFLS, FLS, Custom size (98.4 x 139.7 mm to 320 x 457.2 mm), and Envelopes
Acceptable Paper Weights	Cassette/s: 52 to 220gsm Bypass: 52 to 256gsm Duplex: 220gsm
Print Driver Supported OS	PCL: Windows XP Professional/Windows Vista/Windows 7/Windows 8/Windows 8.1/Windows 2003 Server/Windows 2008 Server/Windows 2012 Server PS: Windows XP Professional/Windows Vista/Windows 7/Windows 8/Windows 8.1/Windows 2003 Server/Windows 2008 Server/Windows 2012 Server/Mac OS x 10.5 to 10.9/Mac OS x 10.6 to 10.10 URFIL: Windows XP Professional/Windows Vista/Windows 7/Windows 8/Windows 8.1/Windows 2003 Server/Windows 2008 Server/Windows 2012 Server/Mac OS x 10.5 to 10.9/Mac OS x 10.6 to 10.10 XPS: Windows 7/Windows 8/Windows 8.1/Windows 2008 Server/Windows 2012 Server
Direct Print	Supported Media: USB memory key, Remote UI and Web Access ³ Supported file types: JPEG, TIFF, PDF, XPS ⁴

All specifications subject to change without notice.

¹ 1 watt sleep mode may not be possible in all circumstances. Certain network configurations and options may prevent the device from entering deep sleep.

² Envelope support via standard cassette: 2 only.

³ XPS print from websites is not supported.

⁴ XPS requires DIRECT PRINT KIT (for PDF/XPS)-H1.

⁵ Based on ITU-T Standard Chart No. 1 mode. Please refer to the user guide for more information.

All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.



Scan Specifications

Scan Type	Duplexing Automatic Document Feeder
Acceptable Originals	Sheet, book, three dimensional objects (up to 2kg) Paper Weight: Single-sided scanning: 42 to 128gsm Double-sided scanning: 50 to 128gsm
Scan Resolution (dpi)	Up to 600 x 600dpi
Scanning Speed (A4, 300dpi)	Single-sided 55ipm, double-sided 27.5ipm
Scan Methods	Push Scan: Colour Universal Send functionality is standard. Integration with a range of optional MEAP based capture software adds powerful workflow and conversion capabilities. Please contact your sales representative for further information. Pull Scan: Colour Network Scan Gear. Scanning is instigated from a remote Windows Scan to USB Memory Key: Available on all models Scan to mobiles, internet-connected devices and cloud-based services: A range of solutions is available to provide scanning to mobile devices, internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.
Paper Capacity (80gsm, A4)	100 sheets

Colour Send Specifications

Destinations	E-Mail/Internet FAX (SMTP), Fax (option for C3320/C3330 PC (SMB, FTP, WebDAV)
Address Book/Speed Dials	LDAP (Max. 2000 searchable), Local (Max. 1800 including 200 Speed dials)
File Formats	Standard: TIFF, JPEG, PDF, PDF (Compact), PDF/A1-b Optional: PPTX+, DOCX+, PDF (OCR)+, PDF (Compac+OCR)+, PDF (Reader Extensions)+

Security Specifications

Standard	IP/Mac Address Filtering, IPsec, SNMP V3.0, IEEE 802.1X, Trusted Platform Module (TPM), Secure Print, Hard Disk Drive Password Lock, Data Erase, Universal Login Manager, Department ID, SSO-H, MailboxLite, Access Management System, Adobe Right Management compatibility
Optional	Encrypted Secure Print, Universal Send Security Feature, iR-ADV Security Kit, Removable HDD Kit, Document Scan & Lock Tracking, Encrypted PDF, HDD Encryption, User and Device signatures, Secure Watermarks, MailboxLite.

Fax Specifications (Optional)

Requires	Canon Super G3 FAX Board-AR1
Number of Connection Lines	1

External Staple Finisher (Optional)

Number of Trays	2
Loading Capacity	600 sheets non-stapled, 50 sheets stapled
Paper Weight	52 to 256gsm
Staple Position	Corner Stapling (All 4 corners), Double Stapling
Stapling Capacity	Up to 50 sheets
Dimensions (W x D x H)	662mm x 646mm x 971mm
Weight	Approx. 40.5kg

Inner Finisher (Optional)

Number of Trays	2
Loading Capacity	Standard 600
Paper Weight	52 to 256gsm
Staple Position	Corner, Double
Stapling Capacity	Standard: 50 sheets On Demand: 40 sheets ECO Stapling: binds up to 5 sheets
Dimensions (W x D x H)	604mm x 525mm x 188mm
Weight	7.2kg

Booklet Finisher (Optional)

Number of Trays	2
Loading Capacity	Upper Tray: 1,000 sheets + Lower Tray: 1,000 sheets
Paper Weight	52 to 256gsm
Staple Position	Corner, Double, Booklet
Stapling Capacity	50
Dimensions (W x D x H)	771mm x 657mm x 971mm
Weight	67.5kg

Other Optional Accessories

Canon PCL International Font Set-A1, Canon Direct Print Kit (for PDF)-H1, Canon Direct Print Kit (for XPS)-H1, Canon Barcode Printing Kit-D1, Canon Universal Send Advanced Feature Set-D1, Canon Universal Send Security Feature Set-D1, Canon Universal Send Digital User Signature Kit-C1, Canon Secure Watermark-B1, Canon Document Scan Lock Kit-B1, Canon Remote Fax Kit-A1, Canon ADF Access Handle-A1, Canon HDD Data Encryption Kit-C9, Canon Encrypted Printing Software-D1, Access Management Kit-B1, Canon Web Access Software-H1, Canon IC Card Reader Box-A1, Canon Serial Interface Kit-K2, Canon Copy Control Interface Kit-A1, Canon Mainbody Heater-A1, Canon Reader Heater-C1

canon.com.au/business
Follow us on Twitter @CanonBusinessAU
1800 444 199

3729-v1-7/15

achieve more.
beyond technology.